



Flour Mesh Specifications PA- XX Series

Specification	Mesh Opening (um)	Thread Diameter (um)	Tram Silk (um)	Warp/weft (cm)	Open Area (%)
PA-3xx	300	100+2*60	100	24.0/25.0	54
PA-4xx	280	100+2*60	100	25.5/26.5	53
PA-5xx	250	100+2*60	90	27.5/29	51
PA-6xx	214	90+2*60	90	32/34	49
PA-7xx	199	80+2*60	80	33/36	48
PA-8xx	181	80+2*60	70	36/40	46
PA-8.5xx	160	70+2*60	70	40/43.5	44
PA-9xx	146	70+2*60	64	43/48	44
PA-9.5xx	140	60+2*60	60	43.0/50.0	43
PA-10xx	130	60+2*50	64	49/52	44
PA-10.5xx	125	60+2*50	60	48.5/54.0	40
PA-11xx	120	60+2*50	48	53/60	42
PA-12xx	112	60+2*50	48	55/63	40
PA-12.5xx	106	60+2*43	48	56.0/64.0	40
PA-13xx	100	60+2*50	48	58/68	58
PA-14.5xx	90	50+2*43	50	62.5/71.5	37
PA-15xx	88	50+2*43	48	65/74	34
PA-17xx	80	50+2*43	43	68.0/81.0	35
PA-20xx	75	50+2*43	43	70.0/84.7	34
PA-21xx	71	50+2*43	43	74.0/87.7	33
PA-25xx	63	43+2*43	43	78.0/94.0	30

Copyright 2004-2017- Shijiazhuang Gezi Screen Mesh Co., Ltd

www.screenmeshchina.com

www.geziexport.com

sales@geziexport.com

Call us: +86 311 69016254